

AMENDMENTS TO CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A dustproof structure for a sleeve bearing, comprising:
 - an axial tube having a tubular body, said axial tube engaging a motor stator;
 - a sleeve bearing mounted in the axial tube, the sleeve bearing including an axial hole through which to extend a shaft of a motor rotor;
 - a dustproof cushion received in the axial tube and attached to an end surface of the sleeve bearing for preventing foreign dust from entering into a gap formed between an inner circumference of the axial tube and an outer circumference of the sleeve bearing, the dustproof cushion including an axial hole through which to extend the shaft of the motor rotor; and
 - at least one oil returning groove ~~being~~ formed on a surface of the dustproof cushion facing the end surface of the sleeve bearing and adapted to re-lubricate an inner circumference of the axial hole of the sleeve bearing.
2. (Currently Amended) The dustproof structure for a sleeve bearing as defined in Claim 1, wherein the oil-returning groove is recessed on the surface of the dustproof cushion and radially extended.
3. (Currently Amended) The dustproof structure for a sleeve bearing as defined in Claim 1, wherein the dustproof cushion includes ~~the~~ an annular wall ~~projected upward that projects upwardly~~ from an inner ~~periphery~~ periphery of the axial hole to ensure that the entire structure is relatively rigid and strong.

4. (Original) The dustproof structure for a sleeve bearing as defined in Claim 1, wherein the dustproof cushion includes a buffer space connected with an end of the oil-returning grooves proximate the axial hole.

5. (Currently Amended) The dustproof structure for a sleeve bearing as defined in Claim 1, wherein the sleeve bearing includes an oil-returning groove on ~~the~~ an end surface.

6. (Currently Amended) The dustproof structure for a sleeve bearing as defined in Claim 5, wherein the sleeve bearing includes two oil-returning grooves on ~~its~~ two end surfaces, and the oil-returning grooves further ~~connects~~ connect to an oil-guiding groove longitudinally extended on ~~the~~ an outer circumference of the sleeve bearing.

7. (Currently Amended) ~~The~~ A dustproof structure for ~~the~~ a sleeve bearing ~~as defined in Claim 1, wherein comprising:~~

an axial tube having a tubular body;

a sleeve bearing mounted in the axial tube, the sleeve bearing including an axial hole through which to extend a shaft of a motor rotor; and

~~the~~ a dustproof cushion ~~is~~ fittingly mounted in the axial tube, the dustproof cushion ~~is~~ being further spaced a predetermined distance from ~~the~~ an end surface of the sleeve bearing so that an oil-returning channel is formed between the end surface of the sleeve bearing and the dustproof cushion.

8. (Currently Amended) ~~The~~ A dustproof structure for ~~the~~ a sleeve bearing ~~as defined in Claim 1, wherein comprising:~~

an axial tube having a tubular body;

a sleeve bearing mounted in the axial tube, the sleeve bearing including an axial hole through which to extend a shaft of a motor rotor; and

~~the~~ a dustproof cushion ~~is~~ integrally formed with the axial tube, the dustproof cushion ~~is~~ being further spaced a predetermined distance from ~~the~~ an end surface of the sleeve bearing so

that an oil-returning channel is formed between the end surface of the sleeve bearing and the dustproof cushion.

9. (Currently Amended) The dustproof structure for a sleeve bearing as defined in Claim 1, wherein the dustproof cushion includes an annular engaging wall and an engaging flange thereof; and the annular engaging wall is projected upward projects upwardly from an outer periphery of the dustproof cushion while the engaging flange being extended extends from a top portion of the annular engaging wall.

10. (New) The dustproof structure for a sleeve bearing as defined in Claim 1, wherein the axial tube further includes an outer surface on which to engage the motor stator.

11. (New) The dustproof structure for a sleeve bearing as defined in Claim 7, wherein the axial tube further includes an outer surface on which to engage a motor stator.

12. (New) The dustproof structure for a sleeve bearing as defined in Claim 8, wherein the axial tube further includes an outer surface on which to engage a motor stator.